CAMBIA







Net Weight	Dimensions carton L x W x H	Qty outer carton			
750 grams	20 x 19 x 12 cm	20			

Housing Aluminium, die cast
RAL colour 9004 (Black), 9003 (White)
Fixture type 3-phase track light
Module Luminus LED

Driver Powergear® Ultimate adapter with build-in LED driver

 Lumen output
 1100lm, 2000lm

 CCT
 3000K, 4000K

 CRI
 >90Ra

Beam angles 10º - 60º (adjustable beam angle)

Adapter Powergear® 3-phase ultimate adapter included

Rotatable 350 Tiltable 90º

Expected Lifetime >40.000h (L70/B30) **Photobiological safety** RG1 unlimited

Power factor > 0.9 LOR > 90% Colour consistency 3 SDCM

Warranty 3 years warranty on LED module and driver

LED MODULES

Standard



OPTIONS

Dimmable Casambi





LED MODULE OPTIONS

Description	Lumen	Watt	Lm/W	сст	CRI	Description	Lumen	Watt	Lm/W	сст	CRI
Luminus LED	1100Lm	17W	85	930, 940	>90Ra						
Luminus LED	2000Lm	25W	80	930, 940	>90Ra						

LED modules

Standard: CRI>80 and >90 in CCT 2700K, 3000K, 4000K

Premium White (PW): for fresh white and depth of colour in retail environments

1) Lumen output of LED module (COB)

2) Mentioned wattage applies for the COB only. Mentioned wattage applies for the most efficient CCT. The power of the complete fixture will be slightly higher due to the power consumption of the driver.

3) Values shown are average values and are subject to +/- 10% tolerance (set by international standards). The colour temperature is subject to a tolerance of up to +/- 150 Kelvin compared to the nominal value. Technical data can be changed by Internova without prior notice.

It all starts with light