FUGA





Net Weight	Dimensions carton L x W x H	Qty outer carton			
985 grams	on request	on request			

Housing Tin-plate
RAL colour 9004 (Black), 9003 (White)
Fixture type 3-phase track light

Module Osram 3030

Adapter Powergear® 3-phase adapter included Power factor 0.9

Output 0.9 200lm, 3W

CCT 840 Light direction Straight (180°), cross (90°)

Lens Warranty

Charge time 24 hours
Duration 1 hour

Battery Ni-Cd 3.2V/1500mA **Version** Non-maintained, ma

Non-maintained, manual testing 2x LedLink Optics LL01CR 3 years (not on battery)

LED MODULE OPTIONS

Description	Lumen	Watt	Lm/W	сст	CRI	Description	Lumen	Watt	Lm/W	сст	CRI
Fuga tracklight	200Lm	3W	67	840	>80Ra						

LED modules

Standard: CRI>80 and >90 in CCT 2700K, 3000K, 4000K

Premium White (PW): for fresh white and depth of colour in retail environments

1) Lumen output of LED module (COB)

7) Mentioned wattage applies for the COB only. Mentioned wattage applies for the most efficient CCT. The power of the complete fixture will be slightly higher due to the power consumption of the driver.

3) Values shown are average values and are subject to +/- 10% tolerance (set by international standards). The colour temperature is subject to a tolerance of up to +/- 150 Kelvin compared to the nominal value.
Technical data can be changed by Internova without prior notice.

It all starts with light