


NUVOLA SQUARE



- Housing** Aluminium, die cast
- RAL colour** 9004 (Black), 9003 (White), 9004/9003 (Black/White), 9004/1036 (Black/Gold)
- Fixture type** Surface mounted
- Module** Dim-to-Warm LED module
- Driver** Osram TRIAC dimmable driver
- Lumen output** 900lm
- CCT** DTW 3000K-1800K
- CRI** >90Ra
- Beam angles** 40°
- Rotatable** Cardanic
- Tiltabl** 45°
- Expected Lifetime** >30.000h (L70/B30)
- Photobiological safety** RG1 unlimited
- Power factor** > 0.9
- Colour consistency** 3 SDCM
- Warranty** 5 years warranty on LED module and driver

Net Weight	Dimensions carton L x W x H	Qty outer carton
825 grams	13 x 15 x 13 cm	20

LED MODULE OPTIONS

Description	Lumen	Watt	Lm/W	CCT	CRI	Description	Lumen	Watt	Lm/W	CCT	CRI
Nuvola Square DTW	900Lm	7W	74	1800K-3000K	>90Ra						

LED modules
Standard: CRI>80 and >90 in CCT 2700K, 3000K, 4000K
Premium White (PW): for fresh white and depth of colour in retail environments
1) Lumen output of LED module (COB)
2) Mentioned wattage applies for the COB only. Mentioned wattage applies for the most efficient CCT. The power of the complete fixture will be slightly higher due to the power consumption of the driver.
3) Values shown are average values and are subject to +/- 10% tolerance (set by international standards). The colour temperature is subject to a tolerance of up to +/- 150 Kelvin compared to the nominal value.
Technical data can be changed by Internova without prior notice.

It all starts with light